

Install WireGuard

WireGuard

```
#!/bin/bash
# Update and Upgrade
apt update && apt upgrade -y && apt full-upgrade -y
#WireGuard Installation
apt-get install -y resolvconf sudo wireguard
```

Zum autostarten mit wg-quick: "[systemctl enable wg-quick@CONFIG](#)"

Umbedingt im Service File eintragen: " **Before=apache2.service mariadb.service redis-server.service ssh.service** "

Eigentliche Datei liegt unter /var/run/resolvconf/resolv.conf

Inhalt:

```
# Dynamic resolv.conf(5) file for glibc resolver(3) generated by resolvconf(8)
#     DO NOT EDIT THIS FILE BY HAND -- YOUR CHANGES WILL BE OVERWRITTEN
# 127.0.0.53 is the systemd-resolved stub resolver.
# run "resolvectl status" to see details about the actual nameservers.

nameserver 1.1.1.1
nameserver 1.0.0.1
options timeout:1 attempts:1 rotate
```

Wenn als intern.conf gespeichert:

```
nano /etc/wireguard/intern.conf && wg-quick up intern && systemctl enable wg-quick@intern
```

```
wg-quick@intern.service
```

```
nano /lib/systemd/system/ssh.service
```

Version #11

Erstellt: 26 Dezember 2022 01:40:25 von craftman96

Zuletzt aktualisiert: 20 Juni 2024 09:13:28 von craftman96